

Heubach formulation No. 140-05

04/93

FUNCTION	PRODUCT	PRODUCER	PBW
Epoxy	Epikote 1007, 100%	Shell, today Hexion	25.70
Solvent	Methyl ethyl ketone		15.40
Glycol ether	Butyl glycol		2.60
Solvent	Solvesso 100	Exxon	7.70
<b>Mix until uniform solution prior to addition.</b>			
Solvent	Methyl ethyl ketone		5.50
Glycol ether	Butyl glycol		0.90
Solvent	Solvesso 100	Exxon	2.70
<b>Premix.</b>			
Anticorrosive pigment	HEUCOPHOS® SRPP	Heubach	5.80
Magnesium silicate	Mistron Monomix	Talc de Luzenac	2.65
Titanium dioxide	Finntitan RR 2, today Kemira 650	Kemira	9.35
Antisettling agent	Aerosil 200	Degussa, today Evonik	0.40
<b>Grind.</b>			
Epoxy	Epikote 1007, 100%	Shell, today Hexion	8.30
Solvent	Methyl ethyl ketone		5.00
Glycol ether	Butyl glycol		0.80
Solvent	Solvesso 100	Exxon	2.50
<b>Mix until uniform solution prior to addition.</b>			
Melamine resin	Cymel 1158, 80%	Dyno Cyanamid, today Cytec	4.70
<b>Add while mixing.</b>			
			<b>100.00</b>
<b>SPECIFICATIONS</b>			
PVC in %			13.9
PVC / CPVC			0.3

# HEUCOPHOS<sup>®</sup> VP92103

today HEUCOPHOS<sup>®</sup> SRPP, in coil coating



*Solvent based*

Heubach formulation No. 140-05

04/93

## SPECIFICATIONS

Solids in %	56.0
Vol.-% Anticorrosive pigment reg. pigment/filler	35.0

\* = Registered trademark of Heubach GmbH. Our product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as a guarantee. The processing company must establish the suitability of individual products itself. As their use lies beyond our knowledge and control, we cannot accept any liability relating to the use of our products in particular applications. In addition to that, the legal rights of third parties must always be considered. The specification agreed between the customer and ourselves is the basis upon which our general sales and delivery conditions are set and is the deciding factor concerning any liabilities. Our standard specification is then valid if no specification has been agreed upon between the customer and ourselves.