HEUCOPHOS® SAPP



in 2K Epoxy

later based coatings	Heubach formulation No. 00186		Rev. Number: 01.01 08/
Function	Product	Producer	PBW
Component A		T Tourse.	. 5
Epoxy dispersion	EPI-REZ™ Resin 3520-WY-55	Hexion	27.80
. , .	Demi. water		7.20
Wetting and dispersing agent	DISPERBYK®-190	BYK-Chemie	0.40
Solvent	Benzyl alcohol		0.70
Glycol ether	DOWANOL™ PM	Dow	0.40
Defoamer	DEE FO® PI-40	MÜNZING	0.15
Premix.			
Anticorrosive pigment	HEUCOPHOS® SAPP	Heubach	8.30
Silica/Alumina Ceramic	Zeeospheres™ G-400	Zeeosphere Ceramics	6.15
Muscovite mica	Micro Mica™ W1	Omya	0.80
Wollastonite	10 ES WOLLASTOCOAT®	NYCO Minerals	9.15
Barium sulfate	Albasoft 70	Sachtleben Minerals	6.15
Iron oxide red pigment	BAYFERROX® 222 FM	LANXESS	6.15
Grind with a bead mill.			
Epoxy dispersion	EPI-REZ™ Resin 3520-WY-55	Hexion	9.40
Defoamer	DEE FO® PI-40	MÜNZING	0.10
	Demi. water		2.40
Add while stirring.			
-			
			85.25
Component B			
Curing agent	ANQUAMINE® 419	Evonik	6.40
Glycol ether	DOWANOL™ PM	Dow	1.10
	Glacial acetic acid		0.05
	Demi. water		7.20
Add while stirring.			
			14.75
Mix components A and B the	proughly prior to use.		
			100.0
Specifications			
Vol% Anticorrosive pigment reg. pigment/filler			24.3
PVC in %			36.2
			61.3

Gf-WB02_004-01_01A

Our application information and any other information in this document as well as our product specifications are based on our current state of knowledge at the Revision Date mentioned in the respective document. They are non-binding and cannot be taken as a guarantee. The processing company must establish the suitability of individual products itself. As their use lies beyond our knowledge and control, we cannot accept any liability relating to the use of our products in particular applications. In addition to that, the legal rights of third parties must always be considered. The product specification agreed between the customer and ourselves is the basis upon which our general sales and delivery conditions are set and is the deciding factor concerning any liabilities. Our standard specification is then valid if no specification has been agreed upon between the customer and ourselves.